

## GR\_Analog Time Switches - THE 111Mini ST2HM1 180

Item 010600031 / EAN-Code 1220000330566



### FEATURES

- ▶ 16 A Contacts
- ▶ Captive tripper levers with 2 hour switching time
- ▶ Synchronous drive time clock time clock
- ▶ Compact size

### APPLICATIONS

- ▶ Outdoor Lighting Control
- ▶ Pump Control
- ▶ Septic Treatment



### TECHNICAL DATA

| General                           |                            |
|-----------------------------------|----------------------------|
| Model Number                      | 010600031                  |
| Description                       | THE 111Mini STHM1 180      |
| Country of Origin (Intermatic)    | MEXICO                     |
| Warranty Period                   | 1-Year                     |
| Harmonized Code                   | 9107.00.8000               |
| EAN Code                          | 1220000330566              |
| Control Specifications            |                            |
| Clock Drive Type                  | Synchronous                |
| Mechanism Type                    | Analog/Mechanical          |
| Dimensions                        |                            |
| Product Dimensions (H x W x D) mm | 90 x 17.5 x 60 mm          |
| Product Dimensions (H x W x D) in | 3.54 x 0.688 x 2.36 in     |
| Material Specifications           |                            |
| Color                             | Gray                       |
| Load Ratings                      |                            |
| Resistive                         | 16 A                       |
| Inductive                         | 4 A, 250 VAC               |
| Electrical Specifications         |                            |
| Input Voltage Range(s)            | 220-240 VAC                |
| Accuracy                          | Mains synchronized         |
| Current Output                    | Changeover, Potential-free |
| Input Voltage Frequencies         | 50 Hz                      |

**Display and Format**

|                         |                |
|-------------------------|----------------|
| Shortest switching time | ON/OFF 2 hours |
|-------------------------|----------------|

**Packaging**

|                                       |                          |
|---------------------------------------|--------------------------|
| Shipping Weight (kg)                  | 0.069                    |
| Shipping Weight (lbs)                 | 0.152                    |
| Product Weight (kg)                   | 0.06                     |
| Product Weight (lbs)                  | 0.132                    |
| Unit Carton Dimensions (H x W x D) in | 0.709 x 2.276 x 3.553 in |
| Units Per Pallet                      | 999                      |

**Operating Specifications**

|               |                            |
|---------------|----------------------------|
| Channels      | 1                          |
| Manual switch | Automatic Mode; Fix ON/OFF |
| Program       | Daily Program (ON/OFF)     |

**Environmental Specifications**

|                         |                            |
|-------------------------|----------------------------|
| Temperature (operation) | -25 - 55 °C / -13 - 131 °F |
|-------------------------|----------------------------|

**Standards and Certifications**

|               |    |
|---------------|----|
| Approval mark | CE |
|---------------|----|

**DRAWINGS AND DIAGRAMS**

