

Data Sheet

Updated 2018-10-25

UDR-Plus

Universal door alarm



Functions and application

UDR-Plus is the perfect protection for emergency doors in shops and other public areas.

- Built in siren that fires when the door is forced.
- Easy configuration of siren duration, delays and reset.
- Built in flash to easily identify the forced door. The flash is extra suitable for big shops and areas with many emergency doors.
- Warning signal with low volume to warn if the door, for example, is not locked after evacuation.
- UDR-Plus is an accessory to the stand alone reader A66 (2-1660) and the code lock A04 (2-1040).

Technical Data

Attributes	UDR Plus
Dimensions (HxWxD) mm	155x100x53
Housing	Plastic
Mounting	Wall mounting
Power Supply	10 - 30 V DC
Electrical connection	Screw terminal
Power consumption at rest (W)	< 0.5
Maximum power consumption (W)	1.5
Current consumption at rest @12V (mA)	10
Maximum current consumption @12V (mA)	100
Current consumption at rest @24V (mA)	5
Maximum current consumption @24V (mA)	50
IP classification	IP40
IK classification	IK07
Temperature	-20° to + 50°C
Siren	0-90 dB/m
Signal	0-77 dB/m
Article number	1-9033-1
E number	E5870725

Colored lenses



Green, 1-9033-7

Grey, 1-9033-8