

## Datasheet

### A6U48 - Mid Range UHF Reader Antenna

#### Product Description

This mid range UHF (865-868MHz) system is ideal for the identification of people and vehicles at a distance of up to 6 metres. It operates with UHF credentials with proprietary security encryption.

The A6U48 offers two operating modes: standalone or Wiegand. In standalone mode, outbound connections are via two output relays. The Wiegand mode facilitates smooth integration with access control solutions.

U4GO makes it easy to control secure access to parking facilities, gated communities and campuses. The reader is backed by an interface that can manage up to 7,560 tags and thanks to its own built-in receiver, up to 100 transmitters.


**U4GO**



#### Key Features

- Gate access automation system
- Can be fixed on wall or pole
- Relay or Wiegand outputs
- Up to 6m detection range
- Detects vehicles up to 80 km/h
- Proprietary UHF detection
- Supplied with power supply, pole fixing bracket, and built-in AES128 receiver

 Certification

 DEEE



**RoHS** Certification

 IP55

 -25°C to 80°C

## Product Specifications

<b>Technology:</b>	UHF, Wiegand 26, 30 & 44 bits
<b>Read range:</b>	6m (mid range)
<b>User Limit:</b>	
• Standalone:	7,560 tags
• Wiegand:	Dependent on access control system
• Receiver:	100 transmitters
<b>Frequency:</b>	Reader: 865 - 868 MHz Receiver: 433.92 MHz
<b>Modulation:</b>	Reader: FHSS Receiver: GFSK
<b>Security Level:</b>	Transmission at AES128 encryption
<b>Connection:</b>	RS-485 (Receiver)
<b>Outputs:</b>	Relays, Wiegand
<b>Relays:</b>	2 x 24 Vac (max 48V)
<b>Contacts:</b>	C, NO
<b>Weight:</b>	0.9 kg



## Electrical Specifications

**Power supply:** 110 - 240Vac / 50-60 Hz

## Accessories



**KFMA6U**

Wall fixing bracket for A6U48 reader



**CTU48, ATU48**

Card and sticker credentials for U4GO range



**TX128-E2, TX128-E4**

2 or 4 channel transmitter with AES128 encryption

## Range References

F0103000127	A6U48	U4GO mid range reader antenna, 6m, 865 MHz
F0103000125	A10U48	U4GO long range reader antenna, 10m, 865 MHz