

LM22-L200

21.5" HD LCD Monitor



Features:

- Industrial level LCD panel, suitable for extensive 7x24 continuous works
- High fidelity digital processing, brilliant and vivid video
- Built in stereo speakers and audio amplifier
- Suitable for every video surveillance and security application: displays HDMI/VGA/BNC input
- Auto-switch when VGA or HDMI signal is detected
- Included desk stand is easily removable for standard VESA mounting
- Support HDCVI, HDTV, AHD and CVBS 1080P camera display



Technical Specification

Model

Model	LM22-L200
-------	-----------

System

Diagonal	21.5"(16:9)
Resolution	1920x1080
Backlight	LED
Brightness/Luminance (Standard)	200cd/m ²
Contrast	1000:1
Angle of view	170°/160°(vertical/horizontal)
Response time	5ms

Interfaces

Input	standard	1 HD(support HDCVI, HDTV, AHD, CVBS), 1 VGA, 1 HDMI, 1 BNC, 1USB, 1 Audio
	optional	-
Output	standard	Built in speakers
	optional	-

General

Consumption (Standard)	≤30W
Consumption (Standby)	≤0.5W

Power Supply	AC100~240V (+/-10%), 50/60 Hz
Weight	4.79kg(with base)
Dimensions(no base)	516.60x316.70x51.20mm
Work Environment	Temperature: 0°C~ 40°C
	Humidity: 10%~85%

Accessory

Standard	VGA cable, power cable, pedestal
Optional	Hanging bracket

Dimensions(mm)

