



M-2U-Xeon-1-XL

OEM PowerEdge R740 XL Server Xeon Silver 4210 - 96GB (6x16Gb) - 2xM.2 480GB - 1TB SAS

Additional HDDs 8TB, 12TB or 16TB, fully equipped 8x16TB=128TB

- 1 Intel Xeon Silver 4210 2.2G, 10C/20T, 9.6GT/s, 13.75M Cache, HT (85W) DDR4-2400
 - 1 OEM PowerEdge R740 XL/R740xd XL Motherboard
 - 1 Dual, Hot-plug, Redundant Power Supply 750W
 - 6 16GB RDIMM, 3200MT/s, Dual Rank
 - 1 BOSS controller card + with 2 M.2 Sticks 480GB (RAID 1)
 - 1 1TB 7.2K RPM NLSAS 12Gbps 512e 3.5in Hot-plug Hard Drive, seven slots free
 - 1 No Additional Cable Requested
 - 1 No Internal Optical Drive for x4 and x8 HDD Chassis
 - 2 European Power Cord 220V
 - 1 Blank for 1CPU Configuration
 - 1 iDRAC9, Express
 - 1 iDRAC Group Manager, Disabled
 - 1 iDRAC, Legacy Password
 - 1 iDRAC Service Module (ISM), NOT Installed
 - 1 PERC H750 RAID Controller, full height
 - 1 Intel Integrated Graphics
 - 1 Broadcom 5720 Quad Port 1GbE BASE-T
 - 1 Intel X710-T2L Dual Port 10GbE BASE-T Adapter, PCIe Full Height
 - 1 No Keyboard and Mouse
 - 1 ReadyRails Sliding Rails with Cable Management Arm
 - 1 OS RAID 1, Storage Configured for Request
-
- 1 Mirasys VMS Software Installed
 - 1 USB Recovery Disk Attached
 - 1 Mirasys IOT Windows Server 2016 Standard Embedded
 - 1 5-Years ProSupport and Next Business Day On-Site Service - Keep Your Hard Drive
Warranty – Enterprise drives Hotplug Drives



| | |
|---------------------------------------|--|
| Form Factor 2U | R740 XL |
| Dimensions (H x W x D) (Inches/cm) | 3.4" / 8.6 x 17.1" / 43.4 x 29.0 / 73.7 |
| Min. Weight (lbs/kg) | 63.0 / 28.6 |
| Number of Bays (max) | up to 8 x 3.5" HDD |
| Included Additional Slots | 2 x M.2 480 GB for storage (22x80mm) |
| Power Supply | Hot Plug Power Supply 2x750W with full redundancy option |