



DATA SHEET M-D-DM-i3-2

Computer can be used as Spotter Client in Mirasys VMS System. As a micro size chassis this can be used in places where installation environment is limited. It can be attached to a monitor directly. Average Camera count up to 6.



OptiPlex 5080 Micro XCTO Intel Core i3-10100T -4Gb 1X4Gb - 1x2.5inch 2TB 5400rpm

Form Factor	Micro
Dimensions (H x W x D) (Inches/cm)	7.2" x 1.4" x 7.0" / 18.2 x 3.6 x 17.8
Min. Weight (lbs/kg)	2.6 / 1.18
Number of Bays (max)	1 internal 2.5" HDD
Expansion Slots	1 M.2 for storage (22x80mm or 22x30mm) 1 M.2 for wireless (22x30mm)
Power Supply	130W external PSU (for 35W CPU)



-
- 1 OptiPlex 5080 Micro, 35W

 - 1 Trusted Platform Module (Discrete TPM Enabled)

 - 1 Intel® Core™ i3-10100T (4 Cores/6MB/8T/3.0GHz to 3.8GHz/35W)

 - 1 No Additional Cable Requested

 - 1 4GB 1x4GB 2666MHz or 2933MHz (2933MHz requires Intel Core i7 or above) DDR4 Memory

 - 1 M.2 256GB PCIe NVMe Class 35 Solid State Drive

 - 1 2TB 5400rpm SATA 2.5" HDD (ZR), not expandable

 - 1 Intel® UHD 630 Graphics

 - 2 Integrated Display Port

 - 1 Thermal Pad

 - 1 European Power Cord

 - 1 130 Watt AC Adapter

 - 1 Regulatory Label for OptiPlex 5080 Micro Form Factor

 - 1 Not EPEAT Registered

 - 1 Speaker for OptiPlex MFF

 - 1 Optical Mouse-MS116 - Black

 - 1 No Keyboard Selected

 - 1 M2X3.5 Screw for SSD/DDPE

 - 1 Mirasys VMS Software Installed

 - 1 USB Recovery Disk Attached

 - 1 Mirasys IOT Win10 Ent LTSC 2019 Embedded

 - 1 5 Years ProSupport and Next Business Day On-Site Service - Keep Your Hard Drive warranty - Enterprise drives Hotplug Drives

**CONTACT THE MIRASYS TEAM FOR MORE INFORMATION ON MIRASYS HARDWARE SOLUTIONS.
SALES@MIRASYS.COM**