



APS
HIGH TECHNOLOGY CABLES
& CONNECTIVITY SOLUTIONS

RA19 Network Cabinets 19" Floor Stand, Steel Door



Features

- 15U to 42U high
- 600, 800 or 1000 mm deep
- Steel door
- Grey White or Black colour
- Heavy duty lockable casters available
- Large cut out in base for cable entry
- Swing handle lock
- Full height front and rear adjustable 19" profiles
- 19" profiles marked with U height position
- Removable side panels
- Delivered assembled (flat pack upon request)

Standards of reference and applications

ANSI/EIA-310-E, IEC 60297-2, DIN 41494 Part 1 & 7.

Telecommunication, LAN, FTTx Cabling, CCTV.

Installation Features

Store at +10 to +50 °C

Install at 0 to +50 °C

Operate at : -10 to +70 °C

Design

Material: SPCC Cold Rolled Steel

Door: SPCC Cold Rolled Steel

19" rails: 2.0mm thick

Frame: 2.0mm thick

Side panels: 1.0mm thick

Colour: standard Black RAL9004 (optional grey or white)

Front door lock: single point lock, swing handle

Rear door lock: single point barrel lock

Side door lock: single point barrel lock

Ordering and delivery information

Unit count	Width	Depth	Height	Weight (kg)	Code	STK	GTIN	Assembled	Flat-Pack
15U	600	600	780	44	RA196615SDB			Standard	Upon request
15U	600	800	780	50	RA196815SDB			Upon request	Yes
15U	800	600	780	50	RA198615SDB			Upon request	Yes
15U	800	800	780	60	RA198815SDB			Upon request	Yes
15U	800	1000	780	70	RA198115SDB			Upon request	Yes
18U	600	600	910	48	RA196618SDB			Upon request	Yes
18U	600	800	910	55	RA196818SDB			Upon request	Yes
18U	800	600	910	55	RA198618SDB			Upon request	Yes
18U	800	800	910	64	RA198818SDB			Upon request	Yes
18U	800	1000	910	74	RA198118SDB			Upon request	Yes
22U	600	600	1090	52	RA196622SDB			Upon request	Yes
22U	600	800	1090	62	RA196822SDB			Upon request	Yes
22U	800	600	1090	62	RA198622SDB			Upon request	Yes
22U	800	800	1090	70	RA198822SDB			Upon request	Yes
22U	800	1000	1090	78	RA198122SDB			Upon request	Yes
24U	600	600	1200	80	RA196624SDB			Upon request	Yes
24U	600	800	1200	80	RA196824SDB			Upon request	Yes
24U	800	600	1200	80	RA198624SDB			Upon request	Yes
24U	800	800	1200	80	RA198824SDB			Upon request	Yes
24U	800	1000	1200	90	RA198124SDB			Upon request	Yes
27U	600	600	1310	60	RA196627SDB			Upon request	Yes
27U	600	800	1310	70	RA196827SDB			Upon request	Yes
27U	800	600	1310	70	RA198627SDB			Upon request	Yes
27U	800	800	1310	80	RA198827SDB			Upon request	Yes
27U	800	1000	1310	92	RA198127SDB			Upon request	Yes
32U	600	600	1540	74	RA196632SDB			Upon request	Yes
32U	600	800	1540	85	RA196832SDB			Upon request	Yes
32U	800	600	1540	85	RA198632SDB			Upon request	Yes
32U	800	800	1540	90	RA198832SDB			Upon request	Yes
32U	800	1000	1540	95	RA198132SDB			Upon request	Yes
42U	600	600	1980	90	RA196642SDB	72 265 74	6410072265742	Upon request	Yes

Unit count	Width	Depth	Height	Weight (kg)	Code	STK	GTIN	Assembled	Flat-Pack
42U	600	800	1980	105	RA196842SDB	72 357 59	6410072357591	Upon request	Yes
42U	800	600	1980	105	RA198642SDB	72 357 60	6410072357607	Upon request	Yes
42U	800	800	1980	120	RA198842SDB	72 357 00	6410072357003	Upon request	Yes
42U	800	1000	1980	135	RA198142SDB	72 493 30	6410072493305	Upon request	Yes

Recommended connectivity

Patch panels for copper cabling : PPE24SU

Patch panels for fiber optic cabling : ODF124SCS, ODF124SCS and generally all LIIN-25 series

Cable management : MCRPAS1, MCRPAS2

Extended System Warranty

The APS System Warranty assures the compliance of the system performance to the applicable class of cabling for a period of 25 years. The warranty may be applied for by an accredited APS Partner who has designed and/or installed the entire system.

Every effort has been put so that this document is most reliable and free from errors. However, AP Solutions Oy cannot be considered responsible for any mistake in this document and users should consult AP Solutions Oy for any information needed. AP Solutions Oy reserves the right to make changes to the documents at any time, without prior notice.