

W76567

15 m Dual Technology motion sensor, DT15+/100, English & Italian

Performance Line- Dual Technology

The Performance Line is the line of legacy Guardall motion sensors (PQ15 and DT15 series) and both are intended for the protection of residential and commercial premises.

DT15+ incorporates a highly effective X-band microwave together with well-proven PIR technology. This pairing produces a superb dual technology sensor that greatly improves false alarm immunity.

Featuring an advanced microwave anti-mask system, the sensor detects any attempt to disable operation of one or both alarm channels.

Anti-stealth is a highly intelligent mode that precisely analyses microwave and PIR activity in a room and significantly improves detection in extreme conditions.

This development also combats intrusion attempts using infrared screening materials. A sneak mirror is used to improve catch performance.

It has been designed to be simple to install with three LEDs within the sensor to facilitate efficient analysis of the technologies.

Incorporating unique signature recognition for precise intruder detection, DT15+ is elevated to the next level for security solutions.



Details

- 15 m volumetric coverage
- Microwave anti-mask
- Enhanced DT processing
- Anti-Stealth technology™
- Selectable End Of Line resistances
- Adjustment-free optics
- Redesigned housing shared across platform range
- Varifocal lens design
- EN50131 Grade 3

W76567

15 m Dual Technology motion sensor, DT15+/100, English & Italian

Technical specifications

General

Technology	Dual
Anti masking	Yes
Pet immune	No
Camera	No

Detection

Max. detection range	15 m
Microwave frequency (nom.)	X-band
Max. microwave output (at 1m)	0.011 μ W/cm ² at 1m
Alarm time	3 s
Peak-to-peak ripple immunity	2 V (at 12 VDC)

Wired/wireless

Wired-wireless	Wired
----------------	-------

Inputs/outputs

Alarm relay characteristic	Normally closed (NC), voltage free, solid state relay rated at 30 V dc, 50 mA with a max. 26 ohm ON resistance.
Tamper relay characteristic	Normally closed (NC), voltage free, solid state relay rated at 30 V dc, 50 mA with a max. 26 ohm ON resistance.
Anti mask relay characteristic	Normally closed (NC). Rated at 24V dc, 50mA
Relay configuration	Multiple EOL values
Remote control lines	Walk test

Electrical

Operating voltage	9 to 16 VDC
Power supply type	12 VDC
Current consumption	13 mA at 12 V (quiescent no alarm) 21 mA at 12 V (max All LEDs on)

Physical

Physical dimensions	110 x 66 x 42 mm (H x W x D)
Net weight	135 g
Colour	White

Environmental

Operating temperature	-10 to 55°C
Environment	Indoor

Standards & regulation

EN50131 grade	Grade 3
---------------	---------

Power Supply

Microwave range adjustment	50% to 100% of range via pot adjustment
Fluorescent lights	Microwave channel rejects these to within 2m of an 80W tube
PIR coverage adjustment	Vertically: none required Horizontally: $\pm 5^\circ$ corner mounted
Aux. period	Duration of fault or mask condition.
End of line resistors	Selectable: (Alarm, Tamper, Aux) Option A: Guardall 8k2, 8k2, 8k2 Option B: 1k0, 1k0, 12k Option C: 4k7, 2k2, 2k2 Option D: 6k8, 4k7, 15k
Walk test LED's	RED - Unit alarm GREEN - Microwave channel YELLOW - PIR channel
Remote LED enable	Control of LED indication using Test line
Anti-masking	Indicated on Aux output and LED's if selected
Microwave/PIR trouble	Indicated on LED's if selected
Test Input	Low or open circuit for LED disable, detector supply to activate.

