

## WIRELESS ROOM-TEMPERATURE SENSOR



The Air2-SenseTH100/W temperature and humidity sensor (\*) with wireless connection allows integration of the thermostat function inside the anti-intrusion control panel.

The rear bracket with which it is equipped allows for quick and simple installation by means of a screw or double-sided adhesive tape.

The incorporated 3V CR2032 lithium battery can be replaced by the end user without generating a tamper signal when the casing is opened.

The 4-value programmable hysteresis ensures device efficiency.

It is possible to configure up to 15 probes connectable to the control panel and simultaneously manage up to 15 climate zones equipped with their own independent thermostats.

(\*) The availability of humidity detection depends on the version of the control panels and the Air2-BS200 transceiver.

### Main features of Air2-SenseTH100/W

Operating frequency	868MHz
Communication type	Two-way
Modulation	GFSK
Probes connectable to the control panel	15
Temperature range	-10°C ÷ +60°C
Reading accuracy	±0.3°C
Programmable hysteresis	0.1 / 0.2 / 0.3 / 0.4 °C
Dimensions	55 x 55 x 13 mm
Weight	22 g

### ORDER CODES

**Air2-SenseTH100/W:** Wireless room-temperature sensor.

# AIR2-SENSETH100/W



Centobuchi, via Dei Lavoratori 10  
63076, Monteprandone (AP), ITALY  
Tel. +39 0735 705007 \_ Fax +39 0735 704912

info@inim.biz \_ [www.inim.biz](http://www.inim.biz)

---

Inim distributor's stamp and signature